


CS3000G 3kW x 2 Table-top twin Product Specifications



Maximum Power	7kW
Electrical Supply	415V AC 50HZ 32-amp 3-phase supply + N&E or 32-amp single phase supply (to be specified at time of order)
Cord & Plug	Cord length 1.5m 5-pin 32-amp Commando plug fitted or 3-core 32 amp cable (hardwired, or 32-amp 3 pin plug), 32-amp single phase (UK) Appropriate plug for each export market
Weight	30kg
Dimensions (mm)	W: 415 L: 810 H: 175
Construction	Ceran top, stainless steel casing
Depth of Field	Up to 30mm
Safety Features	Pan detection; boil-dry protection; overheat prevention; clean filter warning
User Interface	Display panel: Clean filter warning; No Pan Present warning; Glass hot warning; Shutdown
Controls	2 x Ergonomically designed knob with precise settings of 1 through 99
Installation	Installation instructions provided
Cooling Clearance	Rear to front ventilation - integral overhand at rear, with easily removed filter
Bespoke Options	Ceran top design - minimum quantity 50
Warranty	2 years parts and labour, excluding case, Ceran top and rear light source
CE	Approved

*Induced Energy Limited operates a continuous programme of product development and improvement.
Product specifications may therefore be subject to change.*