

CS3000Q 3kW x 4 Suited Quad
Model CS3000QF with ventilation tower
Model CS3000QB with integral ventilation
Product Specifications



| | |
|--------------------------|---|
| Maximum Power | 14kW |
| Electrical Supply | 415V AC 50HZ 32-amp 3-phase supply + N&E |
| Cord & Plug | Cord length 2.5m 5-pin 35-amp Commando plug fitted (UK) Appropriate plug for each export market |
| Weight | 60kg |
| Dimensions (mm) | On application |
| Construction | Ceran top, stainless steel casing |
| Depth of Field | Up to 30mm |
| Safety Features | Pan detection; boil-dry protection; overheat prevention; clean filter warning |
| User Interface | Display panel: Clean filter warning; No Pan Present warning; Glass hot warning; Shutdown |
| Controls | 4 x Ergonomically designed knobs with precise settings of 1 through 99 |
| Installation | Installation instructions provided, with acrylic template guide for control panel aperture |
| Cooling Clearance | Model CS3000QF draws air from the sides of the ventilation tower, through easily removed filters. Model CS3000QB draws air from behind and below the housing unit |
| Bespoke Options | Ceran top design - minimum quantity 50 |
| Warranty | 2 years parts and labour, excluding case and Ceran top |
| CE | Approved |

Induced Energy Limited operates a continuous programme of product development and improvement. Product specifications may therefore be subject to change.