

Induced EnergyCS3000DB 3KW Drop In Single

(fitted bezel, square-cut aperture)



Product Specifications

Maximum Power 3KW

Electrical Supply 220V to 240V AC 50Hz and 60Hz 13-amp single phase

Cord & Plug Cord length 1.8m

Moulded 13-amp plug fitted (UK)

Appropriate plug for each export market

Weight 10kg

Dimensions (mm) Drop-in case: 395 x 395 x 170mm

Ceran footprint nominal: 400 x 400mm Ventilation drawer extension: 220mm Front control panel aperture: 350 x 90mm

Counter aperture: 440 x 400mm Stainless bezel: 480 x 480mm

Construction Ceran top, aluminium casing, stainless steel control panel

Depth of Field Up to 30mm

Safety Features Pan detection; boil-dry protection; overheat prevention; clean filter warning

User Interface Display panel: Clean filter warning; No Pan Present warning; Glass hot warning;

Shutdown

Controls Ergonomically designed knobs with precise settings of 1 through 99

Installation Installation instructions provided

Cooling Clearance The unique drawer concept includes integral ventilation ducts, providing effective

front-to-front ventilation and cooling

Bespoke Options Ceran top design - minimum quantity 50

Warranty 2 years parts and labour, excluding case, Ceran top

CE Approved

Induced Energy Limited operates a continuous programme of product development and improvement. .Product specifications may therefore be subject to change.

Induced Energy Ltd, Westminster Road, Brackley, Northants. NN137EB
Tel: 01280 705 900 Email:sales@inducedenergy.com

