



Induced Energy

CS3000QT 3KW x 4 Table Top Quad



Product Specification

Maximum Power	14KW	(3 phase requires 32 amps per phase)
Electrical Supply	CS3000QT	415V AC 50Hz 32-amp 3-phase + N&E
	CS3000QT-1	2 x 32amp single phase
Cord & Plug	Cord length 1.8m QT - 5-pin 32-amp Commando plug fitted (UK) QT-1 – 2 x 32-amp single phase, fitted Appropriate plug for each export market	
Weight	60kg	
Dimensions (mm)	780 x 673 x 890mm	
Construction	Ceran top, stainless steel casing	
Depth of Field	Up to 30mm	
Safety Features	Pan detection; boil-dry protection; overheat prevention; clean filter warning	
User Interface	Display panel: Clean filter warning; No Pan Present warning; Glass hot warning; Shutdown	
Controls	4 x Ergonomically designed knobs with precise settings of 1 through 99	
Installation	Installation instructions provided	
Cooling Clearance	Model CS3000QB draws air from behind and below the housing unit	
Bespoke Options	Ceran top design - minimum quantity 50	
Warranty	2 years parts and labour, excluding case, Ceran top	
CE	Approved	

Induced Energy Limited operates a continuous programme of product development and improvement.
.Product specifications may therefore be subject to change.

Induced Energy Ltd, Westminster Road, Brackley, Northants. NN13 7EB
Tel: 01280 705 900 Email:sales@inducedenergy.com



